

S.A. RECASENS

Fábrica de LONAS

OFICINAS:
Travessera de Gracia, 18-20, entlo. 1º 08021 BARCELONA.
Tel. (34) 93 200 27 00. Fax (34) 93 202 19 32
E-mail: caik@recasens.com - adm@recasens.com - export@recasens.com
<http://www.recasens.com>

ALMACENES:
Ausias March, 105, 08013 BARCELONA. Tel. 93 245 70 33. Fax 93 231 23 07
Pza. Seis de Diciembre, 7, 28044 MADRID. Tel. 91 508 00 78. Fax 91 508 38 36
Pol. El Pino Parc, A-3, nave 1, 41016 SEVILLA. Tel. 95 452 02 10. Fax 95 467 74 33

TO WHOM IT MAY CONCERN

CERTIFICATE

S.A. RECASENS CERTIFIES THAT ITS ACRYLIC AWNING FABRIC

RECACRIL®

COMPLIES THE FOLLOWING TECHNICAL FEATURES :

1. SOLIDITY OF COLORS
2. REPELLANCY TO WATER AND WIND
3. RESISTANCE AGAINST CONTAMINATION
4. MAX. TENSILE STRENGTH
5. DIMENSIONAL STABILITY
6. MAX. RESISTANCE TO PUTREFACTION

MATERIAL:	100% SOLUTION DYED ACRYLIC FIBER		
WIDTH:	120 cm / 47" 150 cm, 220 cm, 250 cm. (Optional) : 59" / 86,6" / 98,4"		
WARP STRANDS / FILL PICKS PER CM	31.5 WARP 14.0 WEFT		
WATERC COLUMN :	300 mm. / 11.81		±10 %
WEIGHT :	305 gr./m ² / 9 oz		±3 %
TENSILE STRENGTH:	WARP :	130 Kg/5 cm	±5 %
	WEFT:	70 Kg/5 cm	
TEAR STRENGTH.	WARP:	4 Kg / 8.82 pds	±10 %
	WEFT:	2 Kg / 4.40 pds	
OILREPELLENCE:	5/8		
WATERREPELLENCE:	5/8		
ROLLENGTH:	60 meters / 65.6 yards		
WARRANTY :	5 YEARS		
COLOUR FASTNESS :	7/8 - 8		