

## CARACTERÍSTICAS TÉCNICAS / TECHNICAL FEATURES

FTA - 65

Nº Rev. 3 - 07/14

*Recacril Decorline®*  
Furniture Fabric

**DECORLINE**

Composició / Composition	100% Fibra acrílica teñida en masa / 100% Solution Dyed Acrylic Fibre	
Ancho / Width	152 cm / 60" ± 1%	
Peso / Weight	270 g/m <sup>2</sup> ± 5%	UNE 53352
Acabado / Finish	Acabado especial Infinity para tapicería, anti- manchas, antimoho y resistente al agua / Special finish Infinity for upholstery. Anti-stain, rot-proof and water resistant	
Columna de agua / Water Column	≥150 mm	UNE EN ISO 20811
Repelencia al aceite / Oil Repellency	≥4	
Repelencia al agua / Water Repellency	≥4	
Resistencia a la tracción Urdimbre / Tensile Strength Warp	175 daN / 5 cm ± 5%	UNE EN ISO 13934-1
Resistencia a la tracción Trama / Tensile Strength Weft	70 daN / 5 cm ± 5%	UNE EN ISO 13934-1
Resistencia al desgarro Urdimbre / Tear Strength Warp	8 daN ± 10%	UNE 53326
Resistencia al desgarro Trama / Tear Strength Weft	6 daN ± 10%	UNE 53326
Resistencia a la abrasión (Martindale) / Abrasion Resistance	>40.000 ciclos / cycles	UNE EN ISO 12947-2
Solidez a la luz / Colour Fastness	7-8	UNE EN ISO 105 B02
Longitud de pieza / Roll Length	60 m / 65,64 yds	

Travessera de Gràcia, 18-20, Entro. 1ª - 08021 Barcelona (Spain) - Tel. (+34) 93 200 27 00 · Fax (+34) 93 202 19 32 · www.recasens.com



Technical Specifications			Colour Fastness	
	Texsilk® 190	Texsilk® 250		
Composition	100% Olefin		Light Fastness UNE EN ISO 105-B02:2001 Method 2	7 - 8 (max. 8)
Type of Yarn	Solutions Dyed			
Width	160 cm (Min. 155 cms)		Fastness to rubbing UNE EN ISO 105-X12:1996	4 - 5 (max. 5)
Weight/mt2	190 gr	250 gr	Swimming pool water fastness UNE-EN ISO 105-E03:1997	5 (max. 5)
Finish	Water and Oil Repellent			
Packaging	50 mts Rolls			

Physical Characteristics				
TEXSILK 190			TEXSILK 250	
	Warp	Weft	Warp	Weft
Breaking Strength UNE EN ISO 13934-1	1647 N	740 N	1877 N	980 N
Tear Resistance UNE EN ISO 13937-3	73,9 N	43,18 N	81,40 N	54,20 N
Slippage Resistance (Seam method) Pr EN ISO 13936-2	3 mm	3 mm	2 mm	2 mm
Abrasion Resistance UNE EN ISO 12947 (part 1 & 2) Modificada según BS 2543:1995	20.000 cycles		20.000 cycles	
Piling Resistance UNE EN ISO 12945-2	5 (max)		5 (max )	
Dimensional Change in washing UNE EN 25077:1996	-0,4%	-0,3%	-0,4%	-0,3%
Spraytest UNE EN 24920	5 (max 5)		5 (max 5)	

## Properties



UV Protection: **Protects your skin from sun burning blocking more than 97% of UV rays**  
**UV STANDARD 801 Certificate. Level obtained 80 UPF-UV**



Oeko Tex Certification: **Class 1 (artiles for babies)**  
**Non Allergic, Inert Polymer**



Environment: **100% Recyclable**



Sun Resistance: **Excellent protection against sunlight degradation.**



Colors: **Solution dyed colors offering a very good color stability. Rot-proof**



Resistència a l'aigua: **Finished with TEFLON water repellent product.**